

197Si



Panel	19" (48 cm) TFT Active Matrix LCD, Diagonal Hard Coating (3H), Anti-glare Treatment
Design Line	Standard
Pixel / Dot Pitch	0.294mm x 0.294mm
Viewable Image Size (Diagonal)	
Display Area	376mm x 301mm
Brightness	300 cd/m ² (typ)
Contrast Ratio	700:1
Typ. Response Time (tr+tf)	8 ms
Viewing Angle	Horizontal: CR=10: 150/135 Degrees Vertical: CR=5: 160/160 Degrees
Compatibility	VESA, XGA, SVGA, VGA, Mac®Equipped With VGA Port
Scanning Frequency	Horizontal: 29K~83KHz Vertical: 55~75 Hz
Pixel Frequency	135 MHz
Maximum Resolution	1280x1024@75Hz (Analogue)

Recommended Resolution	1280x1024@60Hz
Resolution Supported	640x400@70Hz, 720x400@70Hz, 832x624@75, 640x480@60/67/72/75Hz, 800x600@56/60/72/75Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz
Colours	16.2M
Signal Input	Video: 0.7Vp-p, RGB analogue, Separate Sync: TTL Level, H/V Sync: Positive / Negative

Connectors	Analogue RGB Signal: 15-pin D-sub Male
-------------------	--

Power Source	Power Input: Universal 100~240VAC, 50/60Hz
Power Consumption	37Watts (Max)
Plug & Play	DDC1/2B
EPA ENERGY STAR ®	
User Control	Control Auto Adjust, Left/Vol-, Right/Vol+, Menu, On/Off
Function	Brightness, Contrast, Focus, Clock, H/V Position, Colour Temp, (Warm, Cool & User) Input Select, OSD H/V, OSD Timeout, OSD Language, Input Signal Information, Reset, Exit
OSD Languages	English, German, French, Spanish, Italian, Portuguese, Chinese, Russian
Speaker	N/A

Emissions Standard	
Regulation	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Pixel Fault Class II, Windows®XP Logo
Other Features	VESA Wall Mountable*, Kensington Security Slot

Dimensions (WxHxD)	Monitor: 422x449x215 Carton: 570x535x230
Weight	Net: 5.0 kgs Gross: 7.0 kgs
Loading Qty w/pallet	20' = 600 pcs 40' = 1260 pcs
Warranty	3 Years Parts & Labour

Note: Specifications are subject to change without notice. *Wall mount arm & bracket not included.

